

LED Fixtures – Vapor Tight

Applications: Parking Garages, Food Service, Cold Storage, Wet Locations

Product Features:

- LED Lighting saves 75% to 90% of Energy
- Replaces inefficient T12 or HID Fixtures with Long-Life LED T8 Tubes
- Ideal for harsh environments and wet locations.
- Glass Reinforced Polyester (GRP) body construction.
- Precision formed white powder-coated reflector.
- High-impact, UV protected clear polycarbonate lens.
- Includes stainless-steel clips and mounting hardware
- **DesignLights Consortium** (DLC) Approved T8 Tubes, Available in multiple wattages
- 50,000 Hour Lifespan
- UL Listed Components, ROHS Compliant

Product Specifications:

- WATTS: 32, 36, 44W (using 2 LED T8 Tubes)
- EFFICACY: ~ 100 Lm/W
- CRI: > 75
- COLOR TEMP: 4000K
- POWER SUPPLY: Internal or External PS
- VOLTAGE: 120-277VAC
- FREQUENCY: 50/60Hz
- POWER FACTOR: > 0.90
- THD: < 15%
- MOUNTING: Surface or Suspension

Warranty: 5 Years

LED-VT



Watts	Lumens	Dimensions (in)
32	~ 3200	6.5" x 50.5" x 4.25"
36	~ 3600	6.5" x 50.5" x 4.25"
44	~ 4400	6.5" x 50.5" x 4.25"

ORDER CODE:

ex) ENV-LED-VT-32-IPS-4K

ENV-LED-VT

Wattage
32, 36, 44

Power Supply
IPS = Internal
EPS = External

Color Temp
4K = 4000K
5K = 5000K

